


















- 1** 4 notch, MIL-STD 1913 picatinny rail
- 2** Hard anodized aluminum upper frame for maximum durability
- 3** Full length precision guide rails for outstanding accuracy
- 4** Visual / tactile loaded chamber indicator
- 5** PVD coated steel slide
- 6** Ambidextrous decocking lever
- 7** Reversible magazine catch
- 8** Hard anodized aluminum lower frame for maximum durability
- 9** Interchangeable rubberized comfort grip system
- 10** Match grade trigger

TECHNICAL SPECIFICATIONS

All specifications subject to change.

	CALIBER 9x19mm		BARREL LENGTH 3.75in / 95.5mm		FRAME MATERIAL Upper: Aircraft grade aluminium Lower: Aircraft grade aluminium
	OVERALL LENGTH 7.3in / 185.6mm		SIGHT RADIUS 5.8in / 150mm		GRIP INSERTS Polymer with rubberized overmold
	OVERALL HEIGHT 5.34in / 135.72mm		SIGHT Front: Iron Rear: Iron		GRIP WIDTH Small: 1.19in / 30.35mm Medium: 1.29in / 32.82mm Large: 1.40in / 35.51mm
	OVERALL WIDTH 1.36in / 34.6mm		ACTION DA/SA with ambidextrous decocking lever or manual safety		MAGAZINE CATCH Left / right - reversible
	WEIGHT (WITHOUT MAGAZINE) 27.86oz / 790g		SLIDE Material: Steel Finish: Black with PVD coating		MAGAZINE CAPACITY 15 rounds (optional 10 round for required states)