


















- | | |
|---|---|
| 1 4 notch, MIL-STD-1913 picatinny rail | 6 Ambidextrous decocking lever |
| 2 Steel upper frame | 7 Reversible magazine catch |
| 3 Full length precision guide rails for outstanding accuracy | 8 Steel lower frame |
| 4 Visual / tactile loaded chamber indicator | 9 Interchangeable rubberized comfort grip system |
| 5 PVD coated steel slide | 10 Match grade trigger |

TECHNICAL SPECIFICATIONS

All specifications subject to change.

	CALIBER 9x19mm		BARREL LENGTH 3.75in / 95.5mm		FRAME MATERIAL Upper: Steel Lower: Steel
	OVERALL LENGTH 7.3in / 185.6mm		SIGHT RADIUS 5.8in / 150mm		GRIP INSERTS Polymer with rubberized overmold
	OVERALL HEIGHT 5.34in / 135.72mm		SIGHT Front: Iron Rear: Iron		GRIP WIDTH Small: 1.19in / 30.35mm Medium: 1.29in / 32.82mm Large: 1.40in / 35.51mm
	OVERALL WIDTH 1.36in / 34.6mm		ACTION DA/SA with ambidextrous decocking lever or manual safety		MAGAZINE CATCH Left / right - reversible
	WEIGHT (WITHOUT MAGAZINE) 28.9oz / 820g		SLIDE Material: Steel Finish: Black with PVD coating		MAGAZINE CAPACITY 15 rounds (optional 10 round for required states)