


















- | | |
|---|---|
| 1 6 notch, MIL-STD-1913 picatinny rail | 6 Ambidextrous decocking lever |
| 2 Hard anodized aluminum upper frame for maximum durability | 7 Reversible magazine catch |
| 3 Full length precision guide rails for outstanding accuracy | 8 Advanced polymer composite lower frame |
| 4 Visual / tactile loaded chamber indicator | 9 Interchangeable rubberized comfort grip system |
| 5 PVD coated steel slide | 10 Match grade trigger |

TECHNICAL SPECIFICATIONS

All specifications subject to change.

	CALIBER 9x19mm		BARREL LENGTH 4.5in / 115mm		FRAME MATERIAL Upper: Aircraft grade aluminium Lower: Advanced polymer composite
	OVERALL LENGTH 8.3in / 210mm		SIGHT RADIUS 6.5in / 165mm		GRIP INSERTS Polymer with rubberized overmold
	OVERALL HEIGHT 5.5in / 140mm		SIGHT Front: Iron Rear: Iron		GRIP WIDTH Small: 1.19in / 30.35mm Medium: 1.29in / 32.82mm Large: 1.40in / 35.51mm
	OVERALL WIDTH 1.36in / 34.6mm		ACTION DA/SA with ambidextrous decocking lever or manual safety		MAGAZINE CATCH Left / right - reversible
	WEIGHT (WITHOUT MAGAZINE) 31.74oz / 900g		SLIDE Material: Steel Finish: Black with PVD coating		MAGAZINE CAPACITY 17+1 rounds (optional / 10+1* round for required states)